02/03/2015 Cleaner Software

> The following configurations are based on Intel motherboards with socket 1150 / 1155 / 1366 / 2011.

The recommended configurations works for SD and HD. The Cleaner works under Windows 7 and 8 (Windows 64 bit only).

The list of the compatible hardware it is open. The hardware vendors update their systems on a regular basis and it is difficult to evaluate every new systems that comes to market.

The most important thing to consider is that the video frame-buffer must be compatible with the motherboard and the rest of your system. Our software will work for sure if the systems are configured correctly.

CPU Socket	MotherBoard	Processor	RAM Memory	Blackmagic Card
Socket 1150 chipset Z87	Asus Z87-K	Intel Core i7 4770k	2 X 4GB	Decklink / Intensity
Socket 1155 chipset Z77	Gigabyte Z77X- UP4-TH Asus SaberTooth Z77	Intel Core i7 3770	2 X 4GB	Decklink / Intensity
Socket 1155	Gigabyte GA-P67A-UD5-B3 GA-Z68X-UD7-B3 Z68MA-D2H-B3	Intel Core i5 2500	2 X 4GB	Decklink / Intensity
Socket 1366	Asus Sabertooth x58 (only 16x PCIe slots)	Intel Core i7 920 – 970	3 X 2GB	Decklink / Intensity
Socket 2011	Asus Sabertooth x79	Intel Core i7 3820–4830	2 X 4GB	Decklink /Intensity

Deltacast configurations					
CPU Socket	MotherBoard	Processor	RAM Memory	Deltacast Card	
Socket 1150 chipset Z87	Asus Z87-K	Intel Core i7 4770k	2 X 4GB	Deltacast DELTA-3G-elp 11 bb	
Socket 2011	Asus Sabertooth x79	Intel Core i7 3820– 4830	2 X 4GB	Deltacast DELTA-3G-elp 11 bb	